

Survey of the East Bdy. of T. 25 N., R. 47 E.

Chains

the ground, for the cor. of secs. 1, 6, 7 and 12,
with brass cap mkd:

T25N	
R47E	R48E
S 1	S 6
S 12	S 7

1922

Dig pits, 18x18x12 ins., in each sec., 3 ft. dist.
Land, nearly level. Small clay hillocks from 1 to 5 ft.
in height and 3 to 10 ft. in diam.
Soil, sandy alkaline loam.
Undergrowth, greasewood, sagebrush, rabbit brush.
No grazing.

North, bet. secs. 1 and 6,

Over level land thru dense undergrowth.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in
the ground, for the $\frac{1}{4}$ -sec. cor. of secs. 1 and 6,
with brass cap mkd:

$\frac{1}{4}$	
S1	S6
1922	

Dig pits, 18x18x12 ins., N. and S. of cor., 3 ft. dist.

89.96 Intersect the Fifth Std. Par. N., East 2.52 chs. distant
from the Std. $\frac{1}{4}$ sec. cor. of sec. 36, T.26N., R. 47 E.
as described in Book "A", T. 26 N., R. 47 E.

At point of intersection,

Set an iron post, 3 ft. long, 3 ins. diam., 28 ins. in
the ground, for the closing corner of Ts. 25 N., Rs.
47 and 48 E., with brass cap mkd:

T26N	R47E
S 36	

S 1	S 6
R47E	R48E

T25N
CC

1922

Dig pits, 18x18x12 ins., E., S. and W. of cor., 3 ft.
distant.