

Subdivision of T. 25 N., R. 47 E.


Chains

34.00 Spur, 100 ft. above draw, projects E., Desc. 30 ft. over NE. slope.

37.00 Small draw, drains E., asc. SE. slope.

40.00 On SE. slope, 40 ft. above draw,

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for the 1/4 sec. cor. of secs. 2 and 3, with brass cap mkd:



Raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.

Continue ascent of gradual SE. slope.

43.00 Small spur, projects E.

50.00 Spur, 60 ft. above 1/4 sec. cor., projects N.60°E., desc. N. slope.

66.30 Dry wash at base of NW. slope, 180 ft. below top of spur, drains NE., continue over gentle rolling NE. and E. slopes.


73.00 Dry wash, drains E.

89.88 On gentle NE. slope,

Intersect Fifth Std. Par. N., East 2.37 chs. distant from the Std. 1/4 sec. cor. of sec. 34, T. 26 N., R. 47 E., as described in Book "A", T. 26 N., R. 47 E.

At point of intersection,

Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for the closing cor. of secs. 2 and 3, with brass cap mkd:



Raise a mound of stone, 2 ft. base, 1 1/2 ft. high, S. of cor.

Land, rolling and broken hilly.

Soil, shallow gravelly and rocky loam, 2nd to 3rd rate.