

Subdivision of T. 25 N., R. 47 E.

Chains

Continue ascent of rocky S. slope.

50.20 Rocky spur ridge, 200 ft. above $\frac{1}{4}$ sec. cor., projects S.70°E. from N.70°W. From this point, Water holes in flat bear S.50°12'E. and S.84°43'E. Desc. abrupt rocky NE. slope.

63.00 Head of draw, 240 ft. below ridge, drains N.60°E., asc. abrupt rocky SE. slope.

80.00 Rocky spur, 230 ft. above draw, projects NE., desc. 270 ft. over abrupt, rocky N. slope.

90.28 Intersect Fifth Std. Par. N., 2.35 chs. East of the Std. $\frac{1}{4}$ sec. cor. of sec. 33, T. 26 N., R. 47 E., as described in Book "A", T. 26 N., R. 47 E.

At point of intersection,

Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for the closing corner of secs. 3 and 4, with brass cap mkd:

T26N	R47E
S 33	

S 4	S 3
T25N	R47E
CC	
1922	

Raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.

Land, rough mountainous.

Soil, shallow rocky loam, coarse texture, 3rd and 4th rate. Numerous outcrops and rock slides.

Undergrowth, sagebrush, yellow top, buck brush. Scattering service berry and clumps of willow along spring branch.

Fair grazing.

From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp., heretofore described,

N.0°03'W., on true line, bet. secs. 32 and 33,

Over rough mountainous land thru dense undergrowth and scattering timber. Over gentle S. slope on top of rocky ridge.