

## Subdivision of T. 25 N., R. 47 E.

## Chains.

79.94 The cor. of secs. 4, 5, 8 and 9.  
 Land, rough mountainous.  
 Soil, shallow rocky loam, 3rd and 4th rate. Numerous  
 rock slides and outcrops.  
 Undergrowth, sagebrush, buck brush, scattering service  
 berry.

Fair grazing.

N.0°03'W., on true line, bet. secs. 4 and 5,  
 Over rough mountainous land thru dense undergrowth and  
 scattering scrub timber. Desc. rocky N. slope.

9.70 Draw, 200 ft. below sec. cor., drains S. of W. 5 chs.  
 thence NW., asc. over rocky SW. slope.

29.80 Spur ridge, 250 ft. above draw, projects N.70°W. from  
 S.60°E., desc. N. slope.

40.00 On N. slope, 250 ft. below spur ridge,  
 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in  
 the ground, for the  $\frac{1}{4}$  sec. cor. of secs. 4 and 5,  
 with brass cap mkd:

$\frac{1}{4}$   
 S5 | S4

1922

Raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W.  
 of cor. Continue descent of broken N. slope.

60.10 Draw, 320 ft. below  $\frac{1}{4}$  sec. cor., drains NW., asc. along  
 rocky W. slope.

73.00 Spur ridge, 70 ft. above draw, projects NW., desc. N.  
 slope.

90.37 On N. slope, 250 ft. below ridge,  
 Intersect Fifth Std. Par. N., East, 2.20 chs. distant  
 from the Std.  $\frac{1}{4}$  sec. cor. of sec. 32, as described  
 in Book "A", T. 26 N., R. 47 E.

At point of intersection,

Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in  
 the ground to solid rock and 12 ins. in a mound of  
 stone, for the closing corner to secs. 4 and 5, with