

INDEPENDENT RESURVEY OF THE FIFTH STD. PAR. N. thru R. 47 E.

Chains

over E. slope.

65.50 Spur, projects N.15°W., desc. over rocky W. slope.

80.00 On NW. slope 200 ft. below spur,

Set an iron post, 3 ft. long, 2 ins. diam., 20 ins. in the ground to solid rock and 12 ins. in a mound of stone, for the Std. cor. of secs. 31 and 32, with brass cap mkd:

SC	
T26N	R47E
S 31	S 32

1922

Raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor. No trace of the old Std. sec. cor.

Land, broken hilly and mountainous.

Soil, shallow gravelly loam, medium texture, rocky subsoil, 2nd to 3rd rate.

Undergrowth, sagebrush, service berry, buck brush.

Timber, scattering juniper and pinon pine.

Fair grazing.

West, along the S. bdy. of sec. 31,

Over broken and mountainous land thru dense undergrowth and scattering timber. Desc. W. slope, 40 ft.

2.00 Draw, drains NE., asc. along E. slope.

6.50 Spur, 50 ft. above draw, projects NW., desc. over NW. slope.

17.80 Dry wash, 130 ft. below spur, drains N.30°W., asc. along N. slope.

25.80 Spur ridge, 40 ft. above wash, projects N.30°W., desc. 140 ft. over W. slope.

34.20 Dry wash, drains N., asc. E. slope thru heavy timber, bears N. and S.

40.00 On E. slope 130 ft. above wash,

Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in the ground, for the Std. ¼ sec. cor. of sec. 31, with brass cap mkd:

SC	
¼ S	31

1922