

. N.

Independent resurvey of a portion of the Fifth Std. Par. N.
thru R. 48 E.

asc.

in

with

s.

s.

row-

s.

th

Chains

from which,

A juniper, 12 ins. diam., bears N.48 $\frac{1}{2}$ °E., 233 lks.

distant, mkd: $\frac{1}{4}$ S36 SC BT

A juniper, 5 ins. diam., bears N.63°W., 160 lks.

distant, mkd: $\frac{1}{4}$ S36 SC BT

No trace of old Std. $\frac{1}{4}$ sec. cor.

40.60 Spur, projects SE., desc. gradual E. slope over gentle rolling land.

80.00 The Std. southeast cor. of T. 26 N., R. 48 E., herein-
before described.

*So here
197*

Land, rolling and broken.

Soil, sandy and gravelly clay loam, 2nd to 3rd rate.

Undergrowth, sagebrush, buck brush.

Timber, scattering scrub juniper.

Good grazing.

SURVEY OF THE EAST BOUNDARY OF T. 25 N., R. 48 E.

From the cor. of Ts. 24 and 25 N., Rs. 48 and 49 E.,

which is an iron post, 3 ins. diam., projecting 12 ins. above ground, firmly set and witnessed as described by the Surveyor General. As this cor. will hereafter refer to R. 48 E. only, I efface markings pertaining to R. 49 E. and destroy bearing trees NE. of cor. Raise a mound of stone, 3 ft. base, 2 ft. high W. of cor.

North, on true line, along the E. bdy. of sec. 36,

Over broken hilly land thru dense undergrowth and scattering timber. Desc. along rocky NW. slope.

6.90 Draw, drains NW.

17.90 Dry wash, drains W., asc. S. slope.

27.80 Spur, 40 ft. above draw, projects W., desc. over gradual N. slope.

39.10 Draw, 30 ft. below spur, drains W.

40.00 On gentle W. slope,

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for the $\frac{1}{4}$ sec. cor. of sec. 36 only, with