

Subdivision of T. 25 N., R. 48 E.

Chains

From the cor. of secs. 1, 2, 35 and 36 on the S. bdy.
of the Tp., which is an iron post, 3 ins. diam., projecting 12 ins. above the ground, firmly set, mkd. and wit. as described by the surveyor general.

N.0°01'W., bet. secs. 35 and 36,

Over broken hilly and mountainous land thru dense undergrowth and medium heavy timber. Over broken W. slope.

6.00 Slope changes to gradual NW.

11.20 Draw, 100 ft. below sec. cor., drains NW.; continue along W. slope.

23.50 Main draw, drains SW., asc. over rocky SE. slope.

40.00 On crest of rounded spur, 170 ft. above draw, projecting NW. and SW. from NE.,

Set an iron post; 3 ft. long, 1 in. diam., 26 ins. in the ground, for the $\frac{1}{4}$ sec. cor. of secs. 35 and 36, with brass cap mkd:

$\frac{1}{4}$
S 35 | S 36
1922

Raise a mound of stone; 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

44.00 Desc. over gradual N. slope thru scrubby juniper timber.

63.90 Draw, 160 ft. below top of spur, drains W., asc. 40 ft. over S. slope.

68.10 Low spur, projects W., desc. over broken N. slope.

80.00 On point of small spur, 100 ft. below low spur, projecting N.,

Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for the cor. of secs. 25, 26, 35 and 36, with brass cap mkd:

T25N R48E
S 26 | S 25
S 35 | S 36
1922

from which,

A juniper, 8 ins. diam., bears N.21 $\frac{1}{2}$ °E., 254 lks.
distant, mkd: T25N R48E S25 BT

A juniper, 4 ins. diam., bears S.44°E., 183 lks.