

Subdivision of T. 25 N., R. 48 E.

Chains

- N.0°02'W., on true line, bet. secs. 2 and 3,
Over rolling land thru dense undergrowth. Asc. gentle
S. slope.
- 2.10 Small wash, drains SW.
- 16.80 Wash, drains SW.
- 26.30 Wash, drains SW.
- 40.00 On gentle S. slope,
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in
the ground, for the $\frac{1}{4}$ sec. cor. of secs. 2 and 3,
with brass cap mkd:
- $\frac{1}{4}$
 S3 | S2
 1922
- Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W.
of cor.
- 45.40 Wash, drains SW.
- 54.90 Spur, 90 ft. above wash, projects SW.
- 64.70 Wash, 50 ft. below spur, drains SW.
- 74.70 Wash, drains SW., asc. gradual S. slope.
- 84.80 Spur, 90 ft. above wash, projects W., desc. broken NE.
slope 40 ft. to
- 87.86 Intersect Fifth Std. Par. N., West 81 lks. distant from
the Std. $\frac{1}{4}$ sec. cor. of sec. 34, hereinbefore described.
At point of intersection,
Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in
the ground, for the closing corner of secs. 2 and 3,
with brass cap mkd:
- T 26N R48E
 S 34

 S3 | S2
 CC
 T25N
 1922
- from which,
- A juniper, 6-ins. diam., bears S.65°E., 10 lks.
distant, mkd: S2 CC BT
- A juniper, 12 ins. diam., bears S.55 $\frac{1}{2}$ °W., 118 lks.
distant, mkd: T25N R48E S3 CC BT