

Subdivision of T. 25 N., R. 48 E.

Chains

- 69.20 Road, bears NW. and SE.  
80.00 The cor. of secs. 3, 4, 9 and 10.  
Land, gentle rolling; general SW. drainage.  
Soil, gravelly clay loam, 3rd rate.  
Undergrowth, shad scale, sagebrush, yellow top. Becomes  
scattering in west half mile.  
Poor grazing.

- 
- N.0°02'W., on true line, bet. secs. 3 and 4,  
Over gentle rolling land thru scattering undergrowth.  
23.80 Road, bears NW. and SE., continue over gentle S. slope  
thru dense undergrowth.  
27.50 Dim road, bears E. and W.  
37.60 Old wood road, bears NE. and SW.  
40.00 On gentle SW. slope,  
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in  
the ground, for the  $\frac{1}{4}$  sec. cor. of secs. 3 and 4,  
with brass cap mkd:

$\frac{1}{4}$   
S 4 | S 3  
1922

- Dig pits, 18x18x12 ins., N. and S. of cor., 3 ft. dist.  
Asc, over rolling SW. slopes, along base of hills.  
63.30 Road, bears E. and W.  
87.80 Intersect Fifth Std. Par. N., West 79 lks. distant, from  
the Std.  $\frac{1}{4}$  sec. cor. of sec. 33, hereinbefore described.  
At point of intersection,  
Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in  
the ground, for the closing corner of secs. 3 and 4,  
with brass cap mkd:

T26N R48E  
S 33  
S 4 | S 3  
CC  
T25N

1922

Raise a mound of stones, 2 ft. base,  $1\frac{1}{2}$  ft. high, S.  
of cor.