

## Subdivision of T. 25 N., R. 48 E.

## Chains

4.10 Main Beowawe-Austin road, bears NW. and SE.

39.98 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for the  $\frac{1}{4}$  sec. cor. of secs. 4 and 9, with brass cap mkd:

$$\begin{array}{r} S\ 4 \\ \frac{1}{4} \\ \hline S\ 9 \\ 1922 \end{array}$$

Dig pits, 18x18x12 ins., E. and W. of cor., 3 ft. dist.

50.50 Old road, bears N. and S.

79.98 The cor. of secs. 4, 5, 8 and 9.

Land, nearly level; slight SW. slope and drainage.

Soil, sandy and gravelly alkaline clay loam. 2nd rate.

Undergrowth, shad scale, sagebrush, greasewood.

Fair grazing.

N.0°03'W., on true line, bet. secs. 4 and 5,

Over nearly level land thru dense undergrowth.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for the  $\frac{1}{4}$  sec. cor. of secs. 4 and 5, with brass cap mkd:

$$\begin{array}{r} \frac{1}{4} \\ S\ 5 \mid S\ 4 \\ 1922 \end{array}$$

Dig pits, 18x18x12 ins., N. and S. of cor., 3 ft. dist.

77.80 Road, bears NW. to Wenban Spring and E.

88.13 Intersect Fifth Std. Par. N., East, 8 lks. distant, from the Std.  $\frac{1}{4}$  sec. cor. of sec. 32, hereinbefore described.

At point of intersection,

Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for the closing corner of secs. 4 and 5, with brass cap mkd:

$$\begin{array}{r} T26N\ R48E \\ S\ 32 \\ \hline S\ 5 \mid S\ 4 \\ CC \\ T25N \\ 1922 \end{array}$$

Dig pits. 18x18x12 ins., E., S. and W. of cor., 3 ft. dist.