

Establishment of the $\frac{1}{4}$ sec. cor. on the North Bdy. of
T. 25 N., R. 48 E.

Chains

Set an iron post, 5 ft. long, 1 in. diam., 28 ins. in the ground, for the $\frac{1}{4}$ sec. cor. of sec. 6 only, with brass cap mkd:

$\frac{1}{4}$ S 6
1922

Dig pits, 18x18x12 ins., E. and W. of cor., 3 ft. dist.

BOUNDARIES OF T. 25 N., R. 48 E.

| Line designated | True bearing | Distances chs | Latitudes | | Departures | |
|--------------------|--------------|------------------|-----------|----------|------------|----------|
| | | | N chs | S chs | E chs | W chs |
| E.bdy. T25NR48E | South | 488.37 | | 488.37 | | |
| S.bdy. T25NR48E | N.89°57'W | 477.98 | ...42 | | | 477.98 |
| W.bdy. T25NR48E | North | 489.96 | 489.96 | | | |
| N.bdy. T25NR48E | East | 37.48 | | | 37.48 | |
| do. | S.89°08'E | 40.33 | | .61 | 40.33 | |
| do. | S.89°15'E | 39.67 | | .52 | 39.67 | |
| do. | S.89°10'E | 40.00 | | .58 | 40.00 | |
| do. | S.89°34'E | 40.00 | | .30 | 40.00 | |
| do. | East | 279.85 | | | 279.85 | |
| Convergency | | | | | .61 | |
| Totals | | 1993.64 | 490.38 | 490.38 | 477.94 | 477.98 |
| | | | 490.38 | | | 477.94 |
| Error in latitude | | | .00 | | | |
| Error in departure | | | | | .04 | |

General Description.

Most of this township lies on a low rolling flat, the general drainage and slope being west and south-west toward the dry lake bed situated in the western portion of the township. This lake bed averages about two miles in width and about four and one-half miles in length within the township and extends several miles in a general south-westerly direction beyond the south boundary. A narrow, broken strip of rolling clay hills borders the lake bed on the east shore line. These hillocks vary in height from 3 to 20 ft. and are covered with a scant growth of greasewood. In the spring and early summer months, the lake bed is covered with water three to twenty inches in depth holding the fine clay or silt-like deposits in suspension. The water is unsuited for stock-watering purposes.