

Survey of the East Boundary of T. 25 N., R. 48 $\frac{1}{2}$ E.

Chains

From the cor. of T. 25 N., Rs. 48 $\frac{1}{2}$ and 49 E., previously described,

North, on true line, bet. secs. 31 and 36,


Over rough mountainous land thru dense undergrowth and scattering scrub timber. Asc. gradual SW. slope.

5.00 Rocky spur, 20 ft. above cor., projects N.60°W., desc. abrupt N. slope.

17.70 Draw, 300 ft. below spur, drains S.70°W., asc. rocky S. slope.

32.00 Spur ridge, 210 ft. above draw, projects N.70°W. from East., desc. broken N. slope.

40.00 On steep, rocky NE. slope, 190 ft. below ridge, Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in the ground, for the $\frac{1}{4}$ sec. cor. of secs. 31 and 36, with brass cap mkd:



Raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor.

From the cor.,

Center of three pinon pines on prominent rounded knoll bears S.68°10'E.

Outlet pipe of spring on steep W. slope bears S.84°E. 14 chains.

(No flow of water from spring)

Continue descent of broken NE. slope.

48.20 Draw, 160 ft. below $\frac{1}{4}$ sec. cor., drains N.60°E., desc. along steep, broken NE. slope.

58.00 Spur, 90 ft. below draw, projects N.30°E., desc. along NW. slope of spur.

62.00 Same spur, projects NW., desc. abrupt, rocky N. slope.

66.22 Wire fence at base of abrupt N. slope, bears E. and W.

68.00 Main draw, 185 ft. below spur, drains W. Small storage reservoir and spring bears S.80°E., 8 chs. distant.

69.50 Road, bears E. and W., asc. abrupt S. slope.

80.00 On rocky SW. slope, 280 ft. above draw,