

Subdivision of T. 25 N., R. 48 $\frac{1}{2}$  E.

Chains

48 $\frac{1}{2}$  and 49 E., with brass cap mkd:

T26N R49E  
S 31  
-----  
S 1 S6  
R48 $\frac{1}{2}$ E R49E  
T25N  
CC  
1922

Dig pits, 18x18x12 ins., E., S. and W. of cor., 3 ft. dist.

Land, gentle rolling. General E. drainage.

Soil, gravelly clay loam, 2nd and 3rd rate.

Undergrowth, sagebrush, shad scale.

Fair grazing.

-----  
SUBDIVISION OF T. 25 N., R. 48 $\frac{1}{2}$  E.

From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., hereinbefore described,

S.89°53'W., on true line, bet. secs. 25 and 36 ( a flag at the cor. of secs. 25 and 36 on the W. bdy. being plainly visible)

Over mountainous land thru dense undergrowth and scattering timber. Desc. abrupt W. slope.

4.75 Head of small draw, 120 ft. below sec. cor., drains SW., continue descent of broken SW. slope, 165 ft. to

14.30 Road, bears NW. and SE. at base of abrupt SW. slope.

15.00 Wire fence, bears NW. and SE., enter cultivated field, same bearing.

19.00 Dry wash, course NW.

23.80 Wire fence, bears NW. and SE., leave field, same bearing and ascend over abrupt NE. slope.

37.20 Small spur, 190 ft. above field, projects NW., desc. W. slope.

40.00 On W. slope, 60 ft. below spur,

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for the  $\frac{1}{4}$  sec. cor. of secs. 25 and 36, with brass cap mkd:

S 25  
 $\frac{1}{4}$   
-----  
S 36

1922