

Subdivision of T. 25 N., R. 48 $\frac{1}{2}$ E.

Chains

53.10 Old road, bears N.30°W. and S.30°E.

78.16 The cor. of secs. 1 and 12.

Land, rolling E. slopes.

Soil, shallow gravelly and rocky clay loam, 3rd rate.

Undergrowth, sagebrush, buck brush, shad scale.

Timber, a few scattering scrub junipers on west half mile.

Good grazing.

 Establishemnt of the $\frac{1}{4}$ sec. cors. on the N. and W. bdys.

of fractional sec. 1, T. 25 N., R. 48 $\frac{1}{2}$ E.

From the $\frac{1}{4}$ sec. cor. of secs. 1 and 12, previously described North, on a blank line, parallel to the E. bdy. of sec. 1, to an intersection with the Fifth Std. Par. N. at a point 2.67 chs. West of the Std. southeast cor. of T. 26 N., R. 48 E., as described in Book "C", T. 25 N., R. 48 E.

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for the $\frac{1}{4}$ sec. cor. of sec. 1 only, with brass cap mkd:

$\frac{1}{4}$ S 1
1922

Dig pits, 18x18x12 ins., E. and W. of cor., 3 ft. dist.

 From the Std. SE. cor. of T. 26 N., R. 48 E., above referred to,

North, on true line, along the E. bdy. of T. 26 N., R. 48 E.

Over gentle rolling E. slopes thru dense undergrowth.

18.60 Old wood road, bears E. and W.

26.88 At a point 40 chs. northing from the SE. cor. of sec. 1,

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for the $\frac{1}{4}$ sec. cor. of sec. 1 only, with brass cap mkd:

$\frac{1}{4}$ S 1
1922

Dig pits, 18x18x12 ins., N. and S. of cor., 3 ft. dist.

Continue over gentle rolling E. slopes.