

## Subdivisions of T. 25 N., R. 49 E.

## Chains

48 $\frac{1}{2}$  and 49 E., with a brass cap marked:

T 25 N	
R 48 $\frac{1}{2}$ E	R 49 E
S 36	S 31

T 24 N

1922

Dig pits, 18 x 18 x 12 ins. N., E., and W. of the post, 3 ft. distant. No bearing trees available and mound of stone impracticable.

Land, rolling hills; drainage, S. in the east portion and NW. in the West.

Soil, gravelly to rocky loam.

Timber, juniper and pinon pine.

Undergrowth, sage, buck and service berry brush.

Good grazing,

-----  
Subdivisions

From the cor. of secs. 35 & 36 on S. Bdy. of Tp. heretofore described.

North on a sectional guide meridian bet. secs. 35 and 36.

Over rolling hills, through scattering timber and undergrowth; asc. along a SE. slope 50 ft. to,

7.70 Spur, projects E.; desc. along an E. slope

16.00 Head of draw, drains E.; asc. along a SE. slope 20 ft. to

23.70 Ridge, bears E. and W.; desc. a N. slope 35 ft. to,

40.00 On a N. slope,

Set an iron post, 3 ft. long and 1 in. in dia., 24 ins. in the ground to solid rock and in a mound of stone, for the  $\frac{1}{4}$  sec. cor., with brass cap marked:

$\frac{1}{4}$	
S 35	S 36
1922	

Raise a mound of stone, 2 ft. base and 1 $\frac{1}{2}$  ft. high, W. of the post: No bearing trees available. Continue over rolling land.

42.15 Wash, 10 lks. wide and 3 ft. deep, drains E.; asc. a S. slope 60 ft. to,