


Subdivisions of T. 25 N., R. 49 E.

Chains
48.30 Wash, 10 lks. wide and 3 ft. deep, drains NW.
78.20 Old road, bears E. and W.
83.25 Intersect the Fifth Standard Parrallel North at a point
18.42 chains S. 89° 44' E. of the standard corner of
secs. 35 and 36, heretofore described. At the point
of intersection,
Set an iron post, 3 ft. long and 2 ins. in dia., 26 ins.
in the ground for the closing corner of secs. 1 and 2,
with a brass cap marked:



Dig pits, 18 x 18 x 12 ins. S., E. and W. of the
post, 3 ft. dist.
Land, level; drainage, NW.
Soil, sandy loam, 1st rate.
Timber, none.
Undergrowth, sage, service berry and buck brush.
Good grazing.

From the cor. of secs. 2, 3, 34 and 35 on the S. bdy. of
the TP. heretofore described, thence
N. 0°01' W. bet. secs. 34 and 35.
Over gently rolling hills, through scattering timber and
dense undergrowth; asc. along a SE. slope to,
2.00 Ridge, bears E. and W.; desc. a N. slope 70 ft. to,
24.50 Draw, drains E.; asc. a S. slope 90 ft. to,
34.20 Spur, projects E.; desc. a N. slope 15 ft. to,
40.00 In the bottom of a depression draining E.
Set an iron post, 3 ft. long and 1 in. in dia., 20 ins.
in the ground to solid rock and in a mound of stone
for the $\frac{1}{4}$ cor. of secs. 34 and 35., with brass cap mkd.:

