

Subdivisions of T. 25 N., R. 49 E.

Chains	Raise a mound of stone, 2 ft. base and $1\frac{1}{2}$ ft. high, N. of the post.
51.60	Wash, 10 lks. wide and 3 ft. deep, drains NE.
53.50	Wash, 10 lks. wide and 3 ft. deep, drains NE.
58.30	Old road, bears NE. and SW.
64.90	Wash, 10 lks. wide and 3 ft. deep, drains N.
74.30	Wash, 10 lks. wide and 3 ft. deep, drains N.
79.84	The cor. of secs. 4, 5, 8 and 9. Land, level, general N. exposure and drainage. Soil, sandy loam, 1st rate. Timber, none. Undergrowth, sage and service berry brush. Good grazing.
	----- N. $0^{\circ} 02'$ W. on true line bet. secs. 4 and 5. Over level land, through dense undergrowth, desc. a gentle N. slope.
10.75	Old road, bears NE. and SW.
40.00	Set an iron post, 3 ft. long and 1 in. in dia., 28 ins. in the ground for the $\frac{1}{4}$ sec. cor., with a brass cap marked: $\begin{array}{c} \frac{1}{4} \\ S\ 5 \quad \quad S\ 4 \\ 1922 \end{array}$ Raise a mound of stone, 2 ft. base and $1\frac{1}{2}$ ft. high, W. of the post.
49.45	Wash, 15 lks. wide and 5 ft. deep, drains E.
84.74	Intersect the Fifth Standard Parallel North at a point 20.19 chains S. $89^{\circ} 59'$ E. of the standard corner of secs. 32 and 33, heretofore described and at the point of intersection, Set an iron post, 3 ft. long and 2 ins. in dia., 28 ins. in the ground for the closing corner of secs. 4 and 5, with a brass cap marked: