

## INDEPENDENT

RESURVEY AND RETRACEMENT OF A PORTION OF THE FIFTH STD. PAR. N.  
thru Rs. 53, 54, 55 and 56 E.

Chains

and 32, with brass cap mkd;

T26N R55E  
SC  
S 31 | S 32

---

1921

and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high,  
N. of cor.

Land, rolling and broken. General E. drainage.

Soil, gravelly and rocky loam, limestone formation,  
3rd and 4th rate.

Undergrowth, sagebrush, shad scale, greasewood.

Timber, a few scattering pinon pine and juniper.

Fair grazing.

-----

West, along the S. bdy. of sec. 31,

Over broken mountainous land thru scattering undergrowth  
and scattering timber. Asc. over rocky E. slope.

15.20 Rocky spur, 155 ft. above cor., projects NE., asc. along  
steep rocky N. slope, 120 ft.

36.00 Spur, projects N., desc. 20 ft. over NW. slope,

38.50 Small draw, drains N., asc. 40 ft. over E. slope.

40.00 On E. slope,

Set an iron post, 3 ft. long, 1 in. diam., 10 ins. in  
the ground to bedrock, and 24 ins. in a mound of stone,  
3 ft. base, for the restored Std.  $\frac{1}{4}$  sec. cor. of sec.  
31, with brass cap mkd:

SC  
 $\frac{1}{4}$  S 31

---

1921

from which,

The point for the old Std.  $\frac{1}{4}$  sec. cor. of sec. 31,  
now destroyed, bears S. 40 lks. distant.

Asc. over rocky E. slope.

44.55 The point, hereinafter determined, for the closing cor.  
of T. 25 N., Rs. 54 and 55 E.

56.90 Rocky spur, 260 ft. above  $\frac{1}{4}$  sec. cor., projects N.30°E.,  
desc. 180 ft. over gradual NW. slope.