


SURVEY OF THE WEST BOUNDARY OF T. 25 N., R. 54 E.

Chains

brass cap mkd:



1921

No accessories to this corner.

76.74 Intersect the Fifth Std. Par. N., S.89°54'W., 1.24 chs. distant from the Std. cor. of sec. 36, T. 26 N., R. 53 E., hereinbefore described.

At point of intersection,

Set an iron post, 3 ft. long, 3 ins. diam., 26 ins. in the ground, for the closing corner of T. 25 N., Rs. 53 and 54 E., with brass cap mkd:

T26N R53E

S 36

S 1 S 6

R53E R54E

CC

T25 N

1921

No accessories to this corner.

Land, level.

Soil, alkaline clay loam, fine texture, 3rd rate.

No vegetation.

DEPENDENT

RESURVEY AND SURVEY OF THE SOUTH BOUNDARY OF T. 25 N., R. 54 E.
Chains

From the cor. of Ts. 24 and 25 N., Rs. 53 and 54 E., hereinbefore described,

East, on retracement line, bet. Ts. 24 and 25 N., searching for old corners at record distances, and setting temp. corners,

237.57 Find no trace of old corner. of secs. 3, 4, 33 and 34.
True Line.

From the cor. of Ts. 24 and 25 N., Rs. 53 and 54 E.,

37.57 East, on **Dependent** Resurvey line, bet. Ts. 24 and 25 N., Over level lake bed, Record distance,

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for the $\frac{1}{4}$ sec. cor. of secs. 6 and 31, with brass cap mkd: