

SURVEY OF THE SOUTH BOUNDARY OF T. 25 N., R. 54 E.

Chains

Set an iron post, 3 ft. long, 2 ins. diam., 20 ins. in the ground to bedrock, and 12 ins. in a mound of stone, 3 ft. base, for the cor. of secs. 1, 2, 35 and 36, with brass cap mkd:

T25N	R54E
S 35	S 36
S 2	S 1
T24N	
1921	

Land, rough mountainous. General N. drainage.

Soil, shallow rocky loam, coarse texture, 3rd and 4th rate.

Undergrowth, sagebrush, buck brush.

Timber, scattering pinon pine and juniper.

Good grazing.

East, bet. secs. 1 and 36,

Over rough mountainous land thru scattering undergrowth and scattering scrub timber. Asc. over broken NW. slope.

16.10 Rocky spur, 260 ft. above sec. cor.; projects N.10°E., desc. 150 ft. over rocky E. slope.

26.90 Draw, drains N., asc. 120 ft. over W. slope.

39.70 Saddle between two peaks on main ridge of Diamond Mountains, bears N.20°E. and S.20°W., desc. over rocky E. slope.

40.00 On E. slope, 20 ft. below top of ridge,
Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground, to bedrock, and 20 ins. in a mound of stone, 4 ft. base, for the $\frac{1}{4}$ sec. cor. of secs. 1 and 36, with brass cap mkd:

S 36
$\frac{1}{4}$ ———
S 1

1921

Deposit a limestone, $\frac{1}{2}$ x 8 x 14 ins., mkd. a cross (x) on top surface, at base of mound and alongside post.