

Subdivisions of T. 25 N., R. 54 E.

Chains

From the cor. of secs. 1, 2, 35 and 36, on the S. bdy.
of Tp.,

N.0°01'W., on true line, bet. secs. 35 and 36,

Over rough mountainous land thru scattering undergrowth
and scrub timber. Desc. over rocky NW. slope.


15.90 Point of rocky spur, projects N.30°W., desc. over rocky
N. slope.

27.90 Draw, 840 ft. below sec. cor., drains N.30°W., desc. over
broken and rocky NW. slope, 80 ft. to spur.

36.50 Spur, projects NW., desc. over N. slope.

40.00 On N. slope, 70 ft. below spur,

Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in
the ground to bedrock, and 20 ins. in a mound of stone,
3 ft. base, for the $\frac{1}{4}$ sec. cor. of secs. 35 and 36,
with brass cap mkd:




Desc. 60 ft. over N. slope.

43.30 Box Spring Creek, 1 lk. wide, 1 in. deep, good water,
course W., asc. 690 ft. over abrupt SE. slope.

76.50 Ridge, bears S.80°W. and N.80°E., desc. 70 ft. over
N. slope.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 14 ins. in
the ground to solid rock, and 20 ins. in a mound of
stone, for the cor. of secs. 25, 26, 35 and 36, with
brass cap mkd:



Land, rough mountainous. General drainage W.

Soil, shallow gravelly and rocky loam, coarse texture,
3rd and 4th rate.

Undergrowth, sabebrush, rabbit brush, buck brush.