

Subdivisions of T. 25 N., R. 54 E.

Chains

Soil, shallow gravelly and rocky loam, coarse texture,  
3rd and 4th rate.

Undergrowth, sagebrush.

Timber, pinon pine and juniper.

Good grazing.

N. 0° 01' W., on a true line, bet. secs. 1 and 2,


Over mountainous land thru scattering undergrowth and  
scrub timber. Over broken W. slope.

1.40 Draw, drains SW., asc. 370 ft. over S. slope.

28.00 Spur ridge, bears S. 40° W., asc. along W. slope of spur.

40.00 On W. slope,

Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in  
the ground, for the 1/4 sec. cor. of secs. 1 and 2,  
with brass cap mkd:



and raise a mound of stone, 3 ft. base, 2 ft. high,  
W. of cor.

Asc. 180 ft. over SW. slope.


58.70 Spur, projects W., desc. 240 ft. over N. slope.

67.30 Draw, drains N. 50° W., asc. 80 ft. along rocky W. slope.

81.05 Intersect Fifth Std. Par. N., West, 4.68 chs. distant  
from the Std. 1/4 sec. cor. of sec. 36, T. 26 N., R.  
54 E., hereinbefore described.

At point of intersection,  
Set an iron post, 3 ft. long, 2 ins. diam., 10 ins. in  
the ground to solid rock, and 20 ins. in a mound of  
stone, 3 ft. base, for the closing cor. of secs. 1

and 2, with brass cap mkd:



and raise a mound of stone, 3 ft. base, 2 ft. high,