

## Subdivisions of T. 25 N., R. 54 E.


Chains

Land, hilly and broken. General S. and SW. drainage.  
 Soil, shallow gravelly and rocky loam, 4th rate.  
 Undergrowth, sagebrush, rabbit brush.  
 Timber, small scrub juniper.  
 Good grazing.

-----  
 N.0°02'W., on true line, bet. secs. 3 and 4,

Over broken and hilly land thru scattering undergrowth  
 and small scrub juniper timber. Asc. 220 ft. over S.  
 slope.

- 11.20 Spur, projects W., desc. 140 ft. over N. slope.  
 17.40 Draw, drains W., asc. over broken W. slope.  
 21.50 Spur, projects W., desc. 110 ft. over NW. slope.  
 30.00 Base of mountainous NW. slope, bears N.15°E. and S.15°W.  
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in  
 the ground, for the  $\frac{1}{4}$  sec. cor. of secs. 3 and 4, with  
 brass cap mkd:



and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high,  
 W. of cor.

Continue over gentle NW. slope thru scattering under-  
 growth.

- 81.15 Intersect Fifth Std. Par. N., West, 4.70 chs. distant  
 from the Std.  $\frac{1}{4}$  sec. cor. of sec. 34, T. 26 N., R.  
 54 E., hereinbefore described.

At point of intersection,

Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in  
 the ground, for the closing corner of secs. 3 and 4,  
 with brass cap mkd:

