


Subdivisions of T. 25 N., R. 54 E.

Chains

77.16 Intersect W. bdy. of Tp., 7 lks. S. of the cor. of secs. 6 and 7, previously described.

Thence S.89°50'E., on true line, bet. secs. 6 and 7, Over barren lake bed.

37.16 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for the 1/4 sec. cor. of secs. 6 and 7, with brass cap mkd:



No accessories to this corner.


77.16 The cor. of secs. 5, 6, 7, and 8.

Land, level.

Soil, sandy alkaline clay loam, fine texture, 2nd rate. No vegetation.

N.0°03'W., on true line, bet. secs. 5 and 6, Over barren lake bed.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for the 1/4 sec. cor. of secs. 5 and 6, with brass cap mkd:



No accessories to this corner.

80.73 Intersect Fifth Std. Par. N., West, 3.82 chs. distant from the Std. 1/4 sec. cor. of sec. 32, T. 26 N., R. 54 E., hereinbefore described.

At point of intersection,

Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for the closing corner of secs. 5 and 6, with brass cap mkd:

