

RESTORATION OF A PORTION OF THE BOUNDARY AND SUBDIVISIONAL
CORNERS OF T. 31 N., R. 59 E.

Chains

of which,

Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock and 12 ins. in a mound of stone, for the restored Std. $\frac{1}{4}$ sec. cor. of sec. 32, with brass cap mkd:

$$\begin{array}{c} \text{SC} \\ \frac{1}{4} \text{ S } 32 \end{array}$$

1922

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

East, on random line, searching for original corners

at 40 chain intervals, none of which were found until at 361.68 Fall 494 links N. of the original Std. corner of Tp. 31 N. Rs. 59 and 60 E., which is a juniper post, $3\frac{1}{2}$ ins. square, 24 ins. in length and with scribe marks distinctly showing on two faces. Faint traces of pits were found N., E. and W. of post.

The true course of this line is N.89°13'W., and the proportionate length of each half mile is 40.19 chains.

At the proportionate point for the Std. cor. of secs. 32 and 33,

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for the restored Std. cor. of secs. 32 and 33, with brass cap mkd:

$$\begin{array}{c} \text{SC} \\ \text{T31N } \text{R59E} \\ \text{S } 32 \text{ } | \text{ S } 33 \end{array}$$

1922

from which,

A grey granite boulder, 3 ft. diam. and extending 3 ins. above the ground, mkd. with a "X B0" near center, bears S.34°W., 17 lks distant.

No other suitable bearing objects within a reasonable distance and impracticable to dig pits.

Retracement of a portion of the subdivisional lines in T. 31 N., R. 59 E.

From the Std. cor. of secs. 32 and 33, hereinbefore