RESTORATION OF A PORTION OF THE SUBDIVISIONAL CORNERS IN . T. 31 N., R. 59 E.

CHAINS of stone, for the cor. of secs. 21 and 28 as subsequently determined, with brass cap mkd: T31N S 28 1922 and raise a mound of stone, 2 ft. base, 1 ft. high, E. of cor. The true course of this line is N.O°21'E., and the distance is 39.72 chains. From the theoretical point for the Std. cor. of secs. 33 and 34 on the S. bdy. of the Tp., North, on random line, searching for original corners at 40 chain intervals, and setting temp. cors. Fall 160 lks. E. of the original 4 sec. cor. of secs. 201.30 21 and 22, which is the stub of a decayed juniper post placed alongside an iron post, 2 in. diam., projecting 15 ins. above ground, firmly set, and mark--HES 1917 from which, A cross (x) on top of grey granite boulder showing 36x24x6 ins. above ground, mkd. T31N R59E x 1/4 S22 BR near NW. corner, bears S.742 E., 42 lks. A cross (x) on top of grey granite boulder showing 40x24x6 ins. above ground, mkd. x 1-HES 195 BR T31N R59E, bears N.58 $\frac{1}{2}$ °W., 34 lks. distant. A cross (x) on top near E. edge of brown granite boulder showing 5x3x3 ft. above ground, mkd. x 1-HES 195 BR, bears N.2°W., 77 lks. distant. Alongside original corner, set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for the restored \frac{1}{4} sec. cor. of secs. 21 and 22, with brass

cap mkd: