

RESTORATION OF A PORTION OF THE SUBDIVISIONAL CORNERS IN
T. 31 N., R. 59 E.

Chains

firmly set, marked:

1917

HES
159 1

Dig pits, 18x18x12 ins., in each sec., 3 ft. distant.

The true course of this line is N.0°04'E. and the length of the south and north half miles are 39.98 and 40.04 chains respectively.

From the cor. of secs. 2, 3, 10 and 11,

N.89°51'E., on random line, bet. secs. 2 and 11,

40.15 No trace of original $\frac{1}{4}$ sec. cor. Set temp. cor.

80.15 Fall 226 lks. N. of the point for the original cor. of secs. 1, 2, 11 and 12 as determined by faint traces of pits and fragments of decayed juniper post.

Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for the restored cor. of secs. 1, 2, 11 and 12, with brass cap mkd:

T31N	R59E
S 2	S 1
S 11	S 12

1922

Dig pits, 18x18x12 ins., in each sec., 3 ft. distant.

The true course of this line is S.88°32'E., and the distance is 80.18 chains.

From the cor. of secs. 1, 2, 11 and 12,

N.0°11'E., on random line,

40.00 No trace of original $\frac{1}{4}$ sec. cor. Set temp. cor.

78.24 Fall 34 lks. E. of the accepted corner of secs. 1, 2,

35 and 36 as pointed out to me by Mr. E. E. Lutts of Arthur, Nevada and now marked by a granite stone,

8x6x4 ins. above ground, firmly set and surrounded by a small mound of stones. Alongside,

Set an iron post, 3 ft. long, 2 ins. diam., 20 ins. in

the ground to solid rock and 12 ins. in a mound of

stone, for the restored cor. of secs. 1, 2, 35 and 36

with brass cap mkd:

T32N	R59E
S 35	S 36
S 2	S 1
T31N	

1922