

DEPENDENT

RESURVEY OF A PORTION OF THE S. BDY. OF T.14 N., R. 69 E.

Chains.	West, on a true line, bet. secs. 2 and 35. Ascend E. slope over rolling land.
31.95	Top of spur, 361 ft. above sec. cor., projects N.E.
40.00	Set an iron post, 3 ft. long, 1 in. in dia., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap mkd. <div>S35 $\frac{1}{4}$ ————— S25 1921</div> 66 ft. below spur, and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, N. of the cor.
44.00	Dry wash, 42 ft. below $\frac{1}{4}$ sec. cor., course N.E.
55.30	Top of spur, 165 ft. above wash, projects N.E.
70.20	Dry wash, 70 ft. below spur, course N.E.
73.70	Top of spur, 40 ft. above wash, projects N.E.
80.00	Shallow wash, 15 ft. below spur, course N.E. Set an iron post, 3 ft. long, 2 ins. in dia., 20 ins. in the ground, in a mound of stone, for the cor. of secs. 2, 3, 34 and 35, with brass cap mkd. <div>T14N R69E S34 S35 S3 S2 T13N 1921</div> Land, rolling. Soil, light sandy and rocky loam. Undergrowth, shadscale. No timber.
----- SURVEY OF A PORTION OF THE S. BDY. OF T.14 N., R. 69 E. -----	
	From the cor. of secs. 2, 3, 34 and 35, West, on a true line, bet. secs. 3 and 34. Ascend N.E. slope over rolling land.
15.00	Top of spur, 66 ft. above sec. cor., projects N.E.
20.00	Dry wash, 10 ft. below spur, course N.E.
40.00	Set an iron post, 3 ft. long, 1 in. in dia., 14 ins. in the ground, in a mound of stone, for the $\frac{1}{4}$ sec. cor., with brass ca p mkd. <div>S34 $\frac{1}{4}$ ————— S3 1921</div>