

SURVEY OF A PORTION OF THE S. BDY. OF T. 14 N., R. 69 E.

Chains.

40.00 Set an iron post, 3 ft. long, 1 in. in dia., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.

S31

S6
1921

55 ft. below spur,
from which

a fir 4 ins. in dia., bears N. 5° W., 19 lks. dist.,
marked $\frac{1}{4}$ S 31 B T

an aspen 8 ins. in dia., bears S. 3° W., 25 lks. dist.,
marked $\frac{1}{4}$ S 6 B T

41.00 Mill Cr., running water, 3 lks. wide, 6 ins. deep,
course N.E. Asc. E. slope through dense mahogany, pinon
pine and cedar.

84.42 Set temp. point for the cor. of T's. 13 and 14 N., R's.
68 and 69 E.

Land, rough mountainous. Soil, sandy and rocky. Under-
growth, sage and scant growth of bunch grass. Timber,
pinon pine, mahogany, cedar, aspen and fir.

SURVEY OF THE WEST BOUNDARY OF T. 14 N., R. 69 E.

From the temp. point for the cor. of T's 13 and 14 N.,
R's. 68 and 69 E.,

North, on a random line, setting temp. points at 40.00
and 80.00 chs.

437.58 Fall 101 lks. W. of the cor. of T's. 14 and 15 N., R's.
68 and 69 E., which is an iron post, 3 ins. in dia.,
marked and witnessed as described by the Surveyor General.
Thence S. 0° 08' W., on a true line, bet. secs. 1 and 6.
Ascend N.E. slope over rolling land, through scattering
cedar and pinon pine timber.

4.90 Top of low spur, 10 ft. above Twp. cor., projects E.

27.50 Dry wash, 48 ft. below spur, course E.

31.20 Top of spur, 20 ft. above wash, projects N.E.