

SUBDIVISIONS OF THE FRAGMENTARY SURVEY OF T. 14 N., R. 69 E.

Chains. cap mkd.

T14N	R69E
S4	S3
S10	
1921	

91 ft. below spur,
and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N.
of the cor.

Continue line and measurement.

West, bet. secs. 4 and 10.

87.26 Intersect E. Bdy. of sec. 9, at a point 8.13 chs. dist.
S. of the cor. of sec. 9, hereinbefore described.

Set an iron post, 3 ft. long, 2 ins. in dia., 18 ins. in
the ground, in a mound of stone, for the closing cor.
for secs. 4 and 10, with brass cap mkd.

S9	T14N	
	S4	c
	S10	C
	R69E	
1921		

Land, rolling. Soil, sandy and gravelly. Undergrowth,
medium growth of sage and shadscale. No timber.

From the closing cor. of secs. 4 and 10,

South, on a true line.

31.87 The $\frac{1}{4}$ sec. cor. for sec. 9, hereinbefore described.

40.00 Set an iron post, 3 ft. long, 1 in. in dia., 27 ins. in
the ground, for the $\frac{1}{4}$ sec. cor. for sec. 10, with brass
cap mkd.

$\frac{1}{4}$
S10
1921

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, E.
of the cor.

From the cor. of secs. 3 and 4,

N. $0^{\circ} 01'$ W., on a true line, bet. secs. 3 and 4.

Ascend S. slope over rolling land.

39.85 Intersect N. Bdy. of Twp., at a point 3.19 chs. W. of the
cor. of secs. 33 and 34, T. 15 N., R. 69 E., which is a
2 in. iron post, marked and witnessed as described by