

Subdivision of T. 5 N., R. 70 E.

Chains

chs. distant from the Std. cor. of Tps. 6 N., Rs. 69 and 70 E., which is an iron post, 3 ins. diam., firmly set, projecting 10 ins. above the surface, properly marked and witnessed by two bearing trees.

At point of intersection, set an iron post, 3 ft. long, 2 ins. diam., 10 ins. in the ground to solid rock and 24 ins. in a mound of stone, 3 ft. base, for the closing corner of secs. 5 and 6, with brass cap marked

T6N R70E
S 31

S 6 S 5

T5N R70E
CC

1923

from which,

A juniper, 14 ins. diam., bears S. 32 1/4° E., 166 lks.

distant, marked T5N R70E S5 CC BT

A juniper, 12 ins. diam., bears S. 11° W., 57 lks.

distant, marked T5N R70E S6 CC BT

Land, rolling and broken mountainous.

Soil, shallow gravelly and rocky loam, with rock subsoil.

Many large surface stones on entire mile.

Undergrowth, sagebrush, buck brush, deer brush, service berry, willow along draws.

Timber, juniper, pinon pine, mahogany.

Excellent grazing.

ESTABLISHMENT OF THE QUARTER-SECTION CORNERS ALONG THE NORTH BDY OF T. 5 N., R. 70 E.

The following described quarter-section corners were placed on line between the Std. section and quarter-section corners of the First Standard Parallel North and were established at mid-point between the closing corners of the section in T. 5 N., R. 70 E. to which they refer with the exception of the quarter-section corner of section 6 which was placed on line and at a westing of 40.00 chs. from the closing corner of