D	ependent	Resurvey of the West Boundary of T. 5 S., R. 71 E.	
	Chains		11
		Soil, rocky and sandy loam.	
		Timber, cedar and pinon.	
		Undergrowth, sagebrush.	
		Fair grazing.	
		N.0°11'W., on true line on east bdy. sec. 1.	
		Desc. NW. slope, over mountainous land, covered with	
		medium growth of cedar and pinon timber, and medium	
		growth of sagebrush undergrowth.	
	0.53	Set iron post, 3 ft. long, 2 ins. diam., 27 ins. in the	
		ground, for the cor. of secs. 6 and 7, with brass	
	^ 9	cap marked	
		Т 5 S	
		R 71 E S 6	
	*	S 7	
		1922	
		from which	
		A cedar, 10 ins. diam., bears N.54°E., 38 lks.	
		dist., mkd. T 5 S R 71 E S 6 B T.	
		A cedar, 6 ins. diam., bears S.862°E., 53 lks.	
		dist., mkd. T 5 S R 71 E S 7 B T.	
	3.50	Spur, projects NW.; continue descent.	
	10.00	Draw, 120 ft. below spur, drains NE.; continue descent.	
	15.40	Telephone line; St. George Utah to Acoma Nevada, bears	
	1 - A - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 -	E. and W.	
	20.00	Draw, 55 ft. below draw, drains NE.; continue descent.	
¥	39.90	The $\frac{1}{4}$ sec. cor. for secs. 1 and 6, which is a granite	
		stone, 8 x 10 x 14 ins. above ground, set in mound of	
		stone, marked and witnessed as described by the	
		surveyor general. I destroy the bearing tree pertain-	
	,	ing to sec. 6, and re-establish this cor as follows:	
		Set iron post, 3 ft. long, 1 in. diam., 27 ins. in the	
		ground, for the $\frac{1}{4}$ sec. cor., for sec. 1 only, with	-
		brass cap marked	
		r. 6 8 C. 7 G. C. 3 C. 7 . 6 Ar ₁	
		S 1 3 Dizz	
	(A) (C)	1922	