

Subdivision of T. 5 S., R. 71 E.

Chains

- 3.90 Draw, drains NE.; asc. along NW. slope.
- 12.30 Spur, 140 ft. above draw, projects NE.; desc. NE. slope.
- 40.00 Set iron post, 3 ft. long, 1 in. diam., 6 ins. in the
the ground, on solid rock, surrounded by mound of
stone, for the $\frac{1}{4}$ sec. cor., with brass cap marked

$$\begin{array}{r} S\ 28 \\ \frac{1}{4} \\ \hline S\ 33 \\ 1922 \end{array}$$

from which

- A pinon 12 ins. diam., bears S. $58\frac{1}{4}^{\circ}$ W., 45
lks. dist., mkd. $\frac{1}{4}$ S 33 B T.
- A pinon 10 ins. diam., bears N. $5\frac{1}{4}^{\circ}$ W., 166
lks. dist., mkd. $\frac{1}{4}$ S 28 B T.

- 61.90 West Fork of the Beaver Dam Wash, a stream of good
clear water, 10 lks. wide, 8 ins. deep, 425 ft.

below spur, drains SW.; asc. SW. slope. Old wagon
road brs. SW. and NE.

- 78.88 Intersect the Nevada and Utah State Bdy., at a point
S. $0^{\circ}11'$ W., 10.16 chs. dist., from the 267th mile post.

At point of intersection

Set iron post, 3 ft. long, 2 ins. diam., 28 ins. in
the ground, for the closing cor. for secs. 28 and
33, with brass cap marked

$$\begin{array}{r} T\ 5\ S \\ R\ 71\ E \\ S\ 28 \\ \hline C\ C \quad U \\ S\ 33 \\ 1922 \end{array}$$

from which

- A cedar 6 ins. diam., bears S. $87\frac{3}{4}^{\circ}$ W., 191
lks. dist., mkd. T 5 S R 71 E S 33 C C B T.
- A cedar 10 ins. diam., bears N. 41° W., 126 lks.
dist., mkd. T 5 S R 71 E S 28 C C B T.

This cor. stands on SW. slope 70 ft. above Wash.

Land, mountainous, general drainage and exposure, NE.

on W. side of wash and W. on the east side of wash.

Soil, sandy loam and rocky and gravelly.

Timber, cedar and pinon.