

Subdivision of T. 5 S., R. 71 E.

Chains

Soil, rocky and gravelly.

Timber, cedar and pinon.

Undergrowth, sage, buck and oak brush.

Fair grazing.

East, on true line, bet. secs. 16. and 21

Asc. NW. slope, over mountainous land, covered with cedar and pinon timber, and medium growth of sage buck and oak brush undergrowth.

3.20 Spur, 15 ft. above cor., projects NE.; desc. NE. slope.

10.20 West Fork of the Beaver Dam Wash, stream of good clear water, 8 lks. wide, 6 ins. deep., 140 ft. below spur, drains SE.; asc. rocky SW. slope. Old wagon road brs NW. and SE.

31.10 Rocky spur, 530 ft. above Wash, projects S.; desc. E. slope.

40.00 Set iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap marked

S 16

 $\frac{1}{4}$

S 21

1922

from which

A pinon 7 ins. diam., bears N. $46\frac{1}{2}^{\circ}$ E., 45 lks.dist., mkd., $\frac{1}{4}$ S 16. B T.A cedar 6 ins. diam., bears S. $10\frac{1}{2}^{\circ}$ E., 88 lks.dist., mkd., $\frac{1}{4}$ S 21. B T.

This cor. stands on E. slope 295 ft. below spur.

50.00 Draw, 200 ft. below cor., drains S.; asc. W. slope.

77.00 Top of ascent, 400 ft. above draw, bears N. and S.

79.85 Intersect Nevada and Utah State Bdy. at a point N. 0° $03'$ E., 2.68 chs. dist., from the 265th. plus 2.23 chs.

mile post. At point of intersection

Set iron post, 3 ft. long, 2 ins. diam., 10 ins. in the ground, on solid rock, surrounded by mound of stone

for the closing cor. for secs. 16 and 21, with brass cap marked