

Subdivision of T. 5 S., R. 71 E.

Chains	slope.
13.00	Draw, drains SW.; asc. along NW. slope.
22.00	Draw, 60 ft. above draw, drains NW.; asc. W. slope.
26.70	Spur, 30 ft. above draw, projects NW.; desc. NE. slope.
29.00	Draw, 20 ft. below spur, drains NW.; asc. SW. slope.
40.00	Set iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground, on solid rock surrounded by mound of stone, for the $\frac{1}{4}$ sec. cor., with brass cap marked
	$\begin{array}{r} S\ 9 \\ \hline \frac{1}{4} \\ S\ 16 \\ 1922 \end{array}$
	from which
	A pinon 10 ins. diam., bears S. $24\frac{3}{4}^{\circ}$ E., 74 lks. dist., mkd. $\frac{1}{4}$ S 16 B T.
	A pinon 6 ins. diam., bears N. 15° W., 11 lks. dist., mkd. $\frac{1}{4}$ S 9 B T.
	This cor. stands on SW. slope, 50 ft. above draw, and 150 lks. S. of sandstone ledge, 25 ft. high, bears E. and W.
52.60	Spur, 100 ft. above cor., projects SW.; desc. SE. slope.
58.00	Draw, 120 ft. below spur, drains SW.; asc. SW. slope.
62.10	Spur, 115 ft. above draw, projects SE.; desc. E. slope.
71.00	Rocky ledge, 10 ft. high, 330 ft. above spur, bears N. and S.; thence over level rocky bench.
79.96	Intersect Nevada and Utah State Boundary, at a point N. $0^{\circ}17'W.$, 2.31 chs. dist., from the 264th mile post.
	At point of intersection
	Set iron post, 3 ft. long, 2 ins. diam., 20 ins. in the ground, on solid rock, surrounded by mound of stone, for the closing cor. for secs. 9 and 16, with brass cap marked
	$\begin{array}{r} T\ 5\ S \\ S\ 9 \\ \hline C\ C \quad U \\ S\ 16 \\ R\ 71\ E \\ 1922 \end{array}$
	from which