


Subdivision of T. 5 S., R. 71 E.

Chains

and flag "A" of triangulation.

34.00 Draw, 30 ft. below rim of canyon, drains SW.; asc. S. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 16 ins. in the ground, on solid rock, surrounded by mound of stone, for 1/4 sec. cor., with brass cap marked.



from which

A cedar, 7 ins. diam., bears N. 32 1/2° E., 22 lks. dist., mkd: 1/4 S 4 B T.

A cedar, 6 ins. diam., bears S. 83 1/2° W., 20 lks. dist., mkd: 1/4 S 5 B T.



This cor. stands on spur, 60 ft. above draw, projects NE.; desc. NE. slope.

44.00 Draw, 10 ft. below spur; drains NE.; ascend gentle S. slope.

63.50 Spur, 50 ft. above draw; projects E.; desc. N. slope.

78.65 Intersect the 1st Standard Parallel South, at a point N. 89°38' E., 3.55 chs. dist., from the Std. 1/4 sec. cor., for sec. 32. At point of intersection

Set an iron post; 3 ft. long, 2 ins. diam., 8 ins. in the ground, on solid rock, surrounded by a mound of stone, for closing cor. for secs. 4 and 5, with brass cap marked.



and deposit a memorial which is a sandstone 3 x 4 x 5 ins. marked with a X at base of monument.

This cor stands on N. slope, 310 ft. below spur.

Land mountainous, general drainage and exposure, N. and S.

Soil, rocky and gravelly.