

## Survey of the subdivisions of T. 14 N., R. 50 E.

Chains. From the cor. of secs. 1, 2, 35 and 36, on the S. Bdy. of the township,  
 N.  $0^{\circ} 01'$  W., bet. secs. 35 and 36.  
 Asc. 40 ft. along broken W. slope of ridge, over mountainous land, through dense pinon pine juniper and scattering mahogany.  
 16.30 Slope changes to NW. Desc. 180 ft.  
 26.70 Dry wash, drains S.  $60^{\circ}$  W. Asc. S. slope 250 ft.  
 40.00 Set an iron post, 3 ft. long, 1 in. in diam., 12 ins. in the ground, and 24 ins. in a mound of stone, for the  $\frac{1}{4}$  sec. cor., with brass cap mkd:

$\frac{1}{4}$   
 S35 | S36

1926

from which

A pinon pine 6 ins. in diam., bears N.  $71-3/4^{\circ}$  E., 33 lks. distant, marked  $\frac{1}{4}$  S36 BT

A pinon pine 6 ins. in diam., bears N.  $45-3/4^{\circ}$  W., 56 lks. distant, marked  $\frac{1}{4}$  S35 BT

Asc. SE. slope 180 ft/

66.40 Top of spur, projects W. Leave dense timber, bears E. and W.; enter scattering timber.

Desc. N. slope 70 ft.

74.90 Dry wash, drains W. Asc. S. slope 80 ft.

80.00 Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, for the cor. of secs. 25, 26, 35 and 36, with brass cap mkd.

T14N | R50E  
 S26 | S25  
 S35 | S36  
 1926

from which

A pinon pine 3 ins. in diam., bears S.  $80\frac{1}{4}^{\circ}$  W., 9 lks. distant, marked BT only

A pinon pine 6 ins. in diam., bears N.  $16^{\circ}$  W., 75 lks. distant, marked T14N R50E S26 BT

No other bearing trees available.

Raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of