

Independent resurvey of the Third Standard Parallel North
through Range 50 East.

Chains. Asc. along NE. slope 210 ft.
56.60 Asc. along N. slope 80 ft.
64.60 Point of spur, projects N. Desc. gradual NW. slope.
69.60 Dry wash, drains NE. Asc. SE. slope 170 ft.
80.00 On rocky SE. slope set an iron post, 3 ft. long, 3 ins.
in diam., 27 ins. in the ground, for the standard cor.
of T. 16 N., Rs. 49 and 50 E., with brass cap mkd.

S	C
T16N	
R49E	R50E
S36	S31
1926	

Raise a mound of stone, 4 ft. base, $2\frac{1}{2}$ ft. high, N. of
the corner. No suitable bearing trees available.
Land, rolling. Soil, rocky and gravelly clay. Undergrowth,
sage; scant growth of grass. Timber, very scattering
juniper and pinon pine on W. 40.00 chs.

Survey of the W. Bdy. of T. 15 N., R. 50 E.

From the cor. of Ts. 14 and 15 N., Rs. 49 and 50 E.,
which is an iron post, 3 ins. in diam., firmly set and
properly marked and witnessed, as described in the field
notes of T. 14 N., R. 50 E.,

North, on a true line, bet. secs. 31 and 36.

Desc. N. slope 30 ft. over rolling mountainous land,
through scattering juniper, pinon pine and mahogany.

2.20 Dry wash, drains E. Asc. S. slope 170 ft.

16.70 Side-wash, drains SW. Asc. along SW. slope 300 ft. to
top of spur.

17.30 Dim road, bears E. and S.

37.00 Top of spur, projects S. 80° W. Desc. NW. slope 50 ft.

40.00 Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in
the ground, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.

S36	S31
1926	

from which