

## Survey of the W. Bdy. of T. 15 N., R. 50 E.

- Chains.  
 66.00 Top of spur, projects N. 60° E. Desc. N. slope 300 ft.  
 81.76 Dry wash, drains E.  
 82.60 Intersect the Third Standard Parallel North, at a point, East, 9.76 chs. distant from the standard cor. of T. 16 N., Rs. 49 and 50 E. At the point of intersection, set an iron post, 3 ft. long, 3 ins. in diam., 27 ins. in the ground, for the closing cor. of T. 15 N., Rs. 49 and 50 E., with brass cap mkd.

T16N	R50E
S31	
S1	S6
R49E	R50E
CC	
T15N	
1926	

Raise a mound of stone, 3 ft. base, 2 ft. high, S. of the cor.

No bearing trees available.

Land, broken mountainous. Soil, rocky and gravelly clay, shallow on higher slopes with many exposed ledges.

Undergrowth, sage; fair growth of grass. Timber, scattering juniper, pinon pine and mahogany.

---

Survey of the subdivisions of T. 15 N., R. 50 E.

---

From the cor. of secs. 1, 2, 35 and 36, on the S. Bdy. of the township, which is an iron post, 2 ins. in diam., firmly set an properly marked and witnessed, as described in the field notes of T. 14 N., R. 50 E., N. 0° 01' W., bet. secs. 35 and 36.

- 2.00 Dry wash, drains SW. Asc. SE. slope 500 ft. over mountainous land, through dense pinon pine, juniper and mahogany.
- 29.50 Top of ridge, bears E. and W. Leave dense timber, bears E. and W.; enter scattering pinon pine. Desc. NE. slope 230 ft.
- 40.00 Set an iron post, 3 ft. long, 1 in. in diam., 20 ins. in the ground, to solid rock, in a mound of stone 16 ins.