

Survey of the Second Standard Parallel North thru R. 50 E.

the Second Standard Parallel where I establish the closing corner of T. 10 N., Rs. 50 and 51 E. The township is subdivided regularly from south to north and from east to west with fractional measurements against the north and west boundaries. Closing section corners were set at the intersection of the meridional lines with the Second Standard Parallel North.

SURVEY OF THE SECOND STANDARD PARALLEL NORTH thru R. 50 E.

The original Std. cor. of T. 11 N., Rs. 49 and 50 E. is a quartzite stone, 12x4x6 ins., above ground, firmly set, marked with 6 grooves on E. and W. faces and 6 grooves and SC on N. face. Along east side of corner, Set an iron post, 3 ft. long, 3 ins. diam., 27 ins. in the ground, with brass cap marked

SC
T11N
R49E R50E
S 36 | S 31.08
1923

from which,

A juniper, 8 ins. diam., bears N.40 $\frac{1}{4}$ °E., 432 lks. distant, marked T11N R50E S31 SC BT

A juniper, 12 ins. diam., bears N.29 $\frac{1}{2}$ °W., 300 lks. distant, marked T11N R49E S36 SCBT

From the above Std. cor., I run East, on true line, along the S. bdy. of sec. 31, Over broken rolling land thru medium dense undergrowth and medium heavy timber. Asc. broken W. slope.

10.00 Draw, drains N.60°W.
32.30 Draw, 50 ft. above corner, drains N.70°W. from E., asc. along gravelly bed of draw.
40.00 The mean of two independent measurements,

By 1st = 39.98 chs.
By 2nd = 40.02 chs.

On north edge of wash in draw, set an iron post, 3 ft.