

Survey of the Second Standard Parallel North thru R. 51 E.

Chains

A juniper, 16 ins. diam., bears N.31 $\frac{1}{2}$ °W., 384 lks.

distant, marked $\frac{1}{4}$ S31 SC BT

A juniper, 10 ins. diam., bears N.79°E., 284 lks.

distant, marked $\frac{1}{4}$ S31 SC BT

Continue over rolling land.

45.00 Low spur, projects N. Continue thru medium heavy timber.

50.00 Small draw, drains N., asc. broken W. slope.

65.55 The closing corner of T. 10 N., Rs. 50 and 51 E. as subsequently determined.

73.50 Main spur, 200 ft. above draw, projects N., desc. broken E. slope thru heavy timber, and scattering undergrowth.

80.00 The mean of two independent measurements,

By 1st = 80.00 chs.

By 2nd = 80.00 chs.

On rocky E. slope, 120 ft. below spur,

Set an iron post, 3 ft. long, 2 ins. diam., 16 ins. in the ground to solid rock and 18 ins. in a mound of stone, 2 ft. base, for the Std. sec. cor. of secs. 31 and 32, with brass cap marked

SC

T11N	R51E
S 31	S 32

1923

from which,

A juniper, 6 ins. diam., bears N.18 $\frac{1}{2}$ °E., 87 lks.

distant, marked T11N R51E S32 SC BT

A juniper, 7 ins. diam., bears N.21°W., 97 lks.

distant, marked T11N R51E S31 SC BT

Land, rolling and broken.

Soil, shallow gravelly and rocky clay loam, rock subsoil,

3rd and 4th rate.

Undergrowth, sagebrush, buck brush.

Timber, juniper, pinon pine, scattering mahogany.

Excellent grazing.

East, on true line, along the S. bdy. of sec. 32,

Over rolling and broken mountainous land thru heavy timber