

SURVEY OF THE BDY. BET. Rs. 51 and 52 E. in T. 9 N.

Chains

North, bet. secs. 1 and 6,

Over rolling sagebrush flat thru dense undergrowth.

15.00 Shallow wash drains SW., asc. gentle S. slope.

19.30 On west slope of small spur projecting S., 40 ft. above
draw, a small reservoir bears N.72°W., continue along
broken W. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 32 ins. in the
ground, for the $\frac{1}{4}$ sec. cor., with brass cap marked

$\frac{1}{4}$

S 1 | S 6

1923

Raise a mound of stone, 3 ft. base, 1 $\frac{1}{2}$ ft. high, W.
of cor.

Asc. gravelly S. slope.

48.50 Flat top of spur, 40 ft. above $\frac{1}{4}$ sec. cor., projects
W. From this point, reservoir bears S.32°W., continue
over nearly level land, thru scattering timber.

68.30 Draw, drains S.60°W.

80.00 On gentle rolling S. slope,
Set an iron post, 3 ft. long, 3 ins. diam., 28 ins. in
the ground, for the cor. of Ts. 9 and 10 N., Rs. 51
and 52 E., with brass cap marked

T10N

R51E R52E

S 36 | S 31

S 1 | S 6

T9N

1923

from which,

A juniper, 4 ins. diam., bears N.78°E., 281 lks.

distant, marked T10N R52E S31 BT

A juniper, 6 ins. diam., bears S.49°E., 137 lks.

distant, marked T9N R52E S6 BT

A juniper, 4 ins. diam., bears S.87 $\frac{1}{4}$ °W., 410 lks.

distant, marked T9N R51E S1 BT

A juniper, 4 ins. diam., bears N.13 $\frac{1}{2}$ °W., 127 lks.