

Subdivisions of T. 10 N., R. 51 E.

Chains

From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., hereinbefore described,

N. $0^{\circ} 01'$ W., on true line, bet. secs. 35 and 36,

Over broken and rough hilly land thru heavy timber and medium dense undergrowth. Desc. broken NE. slope.

5.50 Draw, 50 ft. below sec. cor., drains E., asc. broken S. slope.

14.90 Small spur, 50 ft. above draw, projects S. 60° E., Desc. along broken E. slope.

25.30 Draw drains E. 5 chs. thence S. 70° E., asc. SE. slope.

25.70 Old road bears NW. and SE. 2 chs. thence E.

38.00 Spur projects E., desc. 30 ft. over N. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap marked

$\frac{1}{4}$

S 35 | S 36

1923

from which,

A juniper, 14 ins. diam., bears N. 7° E., 46 lks.

distant, marked $\frac{1}{4}$ S36 BT

A juniper, 8 ins. diam., bears N. $39\frac{1}{4}^{\circ}$ W., 52 lks.

distant, marked $\frac{1}{4}$ S35 BT

Desc. N. slope.

41.70 Dry wash, 10 ft. wide, 4 ft. deep, 50 ft. below $\frac{1}{4}$ sec. cor. drains E. Asc. gradual S. slope.

44.10 Old road, bears E. and W.

51.80 Small gravelly spur projects S. 60° E., desc. NE. slope.

55.20 Draw, 30 ft. below spur, drains SE., asc. SW. slope.

60.30 Spur, 70 ft. above draw, projects S. 60° E., desc. N. slope.

70.00 Draw, 90 ft. below spur, drains E., asc. broken SE. slope.

80.00 On rocky SE. slope, 80 ft. above draw,

Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for the cor. of secs. 25, 26, 35 and 36, with brass cap marked