

## Subdivision of T. 10 N., R. 51 E.

## Chains

- 36.70 Dry channel, 10 ft. wide, 3 ft. deep, drains S.  
 37.10 Old road bears N. and S.  
 40.01 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for the  $\frac{1}{4}$  sec. cor., with brass cap marked

S 11  
 $\frac{1}{4}$  —————  
 S 14  
 1923

Dig pits, 18x18x12 ins., E. and W. of cor., 3 ft. dist.  
 Continue over nearly level land thru very dense undergrowth and very scattering timber. Asc. very gentle E. slope.

- 58.00 Small wash, drains NE.  
 66.60 Draw drains NE., asc. gentle SE. slope, 50 ft.  
 77.60 Slope changes to a gentle SW., desc. 10 ft.  
 80.02 The cor. of secs. 10, 11, 14 and 15.  
 Land, rolling and nearly level.  
 Soil, sandy and gravelly clay loam, medium texture, 3rd rate on slopes; fine sandy alluvial clay loam, fine to medium texture, 2nd and 3rd rate on bottom lands.  
 Soil on bottom lands is slightly alkaline.  
 Undergrowth, sagebrush, yellow top, rabbit brush, buck brush.  
 Timber, no timber on bottom lands; very scattering juniper on the extreme eastern and western portions of mile.  
 Poor grazing.

-----

N. 0°01'W., on true line, bet. secs. 10 and 11.

Over gentle rolling land thru scattering timber and medium dense undergrowth. Asc. 30 ft. over SW. slope.

- 5.50 Spur projects E., desc. 40 ft. over NW. slope.  
 10.21 Intersect Second Standard Parallel North, West 18.21 chs. distant from the Std. cor. of secs. 35 and 36, herein before described.

At point of intersection, on gentle NW. slope,  
 Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in