

Subdivision of T. 10 N., R. 51 E.

Chains

$$\frac{1}{4} \frac{S \ 10}{S \ 15}$$

1923

No suitable bearing trees available, dig pits, 18x18
x12 ins., E. and W. of cor., 3 ft. distant.

Continue descent of gentle NW. slope.

- 41.70 Draw drains NE., asc. gentle SE. slope thru dense under-
growth.
- 49.00 Spur projects NE, 40 ft. above draw. Desc. gentle broken
NW. slope.
- 56.70 Dry wash, 4 ft. wide, 1 ft. deep, drains NE., continue
across gentle NE. slope thru medium heavy timber.
- 65.00 Dry wash, 3 ft. wide, 2 ft. deep, drains NE., asc. 120
ft. over broken SE. slope.
- 79.92 The cor. of secs. 9, 10, 15 and 16.
Land, rolling and broken.
Soil, shallow gravelly and rocky clay loam, medium to
coarse texture, rocky and gravelly subsoil, 3rd and
4th rate.
Undergrowth, sagebrush, buck brush, greasewood.
Timber, juniper, pinon pine.
Fair grazing.
-
- N.0°02'W., on true line, bet. secs. 9 and 10,
Over rough broken hilly land thru medium heavy timber
and medium dense undergrowth. Over broken E. slope.
- 2.00 Spur projects E., desc. N. slope 70 ft.
- 7.40 Draw drains E., asc. gravelly S. slope.
- 10.43 Intersect Second Standard Parallel North, West 18.10 chs.
distant from the Std. cor. of secs. 34 and 35, herein-
before described.
At point of intersection,
Set an iron post, 3 ft. long, 2 ins. diam., 22 ins. in
the ground to solid rock and 12 ins. in a mound of
stone, 2 ft. base, for the closing corner of secs.
9 and 10, with brass cap marked