

Subdivision of T. 10 N., R. 51 E.

Chains

69.20 Spur projects N.30°E., desc. 90 ft. over broken SE. slope.

76.77 The cor. of secs. 7, 8, 17 and 18.

Land, rough broken and heavily rolling.

Soil, shallow gravelly and rocky clay loam, medium to coarse texture, rocky subsoil, 3rd and 4th rate.

Undergrowth, sagebrush, buck brush.

Timber, juniper, pinon pine, mahogany.

Good grazing.

N.0°03'W., on true line, bet. secs. 7 and 8,

Over heavily rolling land thru heavy timber and medium dense undergrowth. Asc. 50 ft. over broken SE. slope.

8.00 Spur projects NE., desc. 20 ft. over rolling NW. slope.

10.75 Intersect Second Standard Parallel North, West 17.59 chs. distant from the Std. cor. of secs. 32 and 33, hereinbefore described.

At point of intersection,

Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for the closing corner of secs. 7 and 8, with brass cap marked

T11N	R51E
S 32	
S 7	S 8
T10N	R51E
CC	
1923	

from which,

A juniper, 8 ins. diam., bears S.37½°E., 200 lks. distant, marked T10N R51E S8 CC BT

A juniper, 10 ins. diam., bears S.74½°W., 41 lks. distant, marked T10N R51E S7 CC BT

Land, rolling and broken.

Soil, shallow rocky clay loam, coarse texture, rock subsoil, 3rd and 4th rate.

Undergrowth, sagebrush, buck brush.

Timber, juniper, pinon pine.

Fair grazing.