

Survey of Portion of 2nd Standard Parallel N., R. 53 E.

Chains

From the standard corner of townships 11 north, ranges 52 and 53 east, just described.

East, on S. bdy. sec. 31.

Over gently rolling land, through scattered timber and medium undergrowth.

36.50 Shallow wash, drains SE.

40.00 Set an iron post, 3 ft. long, 1 in. dia., 18 ins. in the ground, and supported by a mound of stone, for standard $\frac{1}{4}$ sec. cor., with brass cap marked

SC
 $\frac{1}{4}$ S31

1925

from which

A pinon, 4 ins. diam., bears N. $21\frac{1}{2}^{\circ}$ E., 542 lks. dist., marked $\frac{1}{4}$ S31 SC BT

No other accessories available.

44.00 Road, bears NW. and SE.

59.09 Point for the closing cor. of Ts. 10 N., Rs. 52 and 53 E.

80.00 Set an iron post, 3 ft. long, 2 ins. dia., 18 ins. in the ground to bedrock, and supported by a mound of stone, for standard cor. of secs. 31 and 32, with brass cap marked

SC
T11N | R53E
S31 | S32

1925

from which

A juniper, 6 ins. diam., bears N. $33\frac{1}{2}^{\circ}$ E., 85 lks. dist., marked T11N R53E S32 SC BT

A juniper, 5 ins. diam., bears N. 57° W., 186 lks. dist., marked T11N R53E S31 SC BT

Land, gently rolling with a slight E. and SE. exposure and drainage.

Soil, gravelly and scattered rock; 2nd and 3rd rate.

Timber, scattered juniper and pinon.

Undergrowth, medium dense sagebrush.