Subdivision of T. 10 N., R. 52 E.

Chains	
27.20	Draw, 40 ft. deep, drains SE.
35.50	Top of low rise, bears N.20°W. and S.20°E.; descend 35 ft. to
40.02	In draw, drains SE., and 350 ft. above sec. cor., Set an iron post, 3 ft. long, 1 in. dia., 27 ins. in the ground, for ¼ sec. cor., with brass cap marked ¼ S10/S15 1925 from which A pinon, 12 ins.diam.,bears N.18°W., 34 lks. dist.,marked ¼ S10 BT A pinon, 4 ins.diam.,bears S.60½°W., 108 lks. dist.,marked ¼ S15 BT
49.00	Spur, 215 ft. above ¼ sec. cor., projects SE.; descend broken SW. slope, 330 ft. to sec. cor.
80.04	The cor. of secs. 9, 10, 15 and 16. Land, rolling mountainous; SE. and SW. exposures; drainage SE. Soil, rocky and gravelly loam; 3rd rate. Timber, scattered to medium dense juniper and pinon. Undergrowth, sagebrush and shadscale.
	———
	N. 0°02' W., on true line bet. secs. 9 and 10. Over mountainous land through medium timber and undergrowth; ascending 90 ft. over SW. slope to
10.14	Intersect 2nd standard parallel north, West, 21.11 chs. dist. from the standard cor. of secs. 34 and 35, heretofore described. At point of intersection, Set an iron post, 3 ft. long, 2 ins. dia., 28 ins. in the ground, for closing cor. of secs. 9 and 10, with brass cap marked T11NR52E S34 S9 | S10 T10N | R52E CC 1925 from which