

SURVEY OF THE S. BDY. T. 14 N., R. 52 E.

CHAINS

40.00 Set an iron post, 3 ft. long, 1 in. dia., 20 ins. in the ground to solid rock, in a mound of stone, for 1/4 sec. cor., with brass cap mkd

1/4 S 32
S 5
1924

At base of post deposit a marked(x)stone 1x2x2 ins.

48.00 Dry surface wash, drains SE.

62.00 Low spur, projects S.

80.00 Set an iron post, 3 ft. long, 2 ins. dia., 18 ins. in the ground to solid rock, in a mound of stone, for the cor. of secs. 5, 6, 31 and 32, with brass cap mkd

T14NR52E
S31 S32
S6 S5
T13N
1924

At base of post deposit a marked(x)stone 1x2x2 ins.

Land, rolling bench. Soil, gravelly loam.

Timber, none. Undergrowth, sagebrush.

Fair grazing. General drainage, SE.

West, bet. secs. 6 and 31
Over rolling bench land

19.90 Dry surface wash, drains SE.

40.00 Set an iron post, 3 ft. long, 1 in. dia., 16 ins. in the ground to solid rock, in a mound of stone, for 1/4 sec. cor., with brass cap mkd

1/4 S 31
S 6
1924

At base of post deposit a marked(x)stone 1x2x2 ins.

78.24 On level bench

Set an iron post, 3 ft. long, 3 ins. dia., 27 ins. in the ground, for the cor. of Tps. 13 and 14 N., Rs. 51 and 52 E., with brass cap mkd