

## SURVEY OF W. BDY. T. 18 N., R. 54 E.

CHAINS SW. slope 230 ft. to sec. cor. .  
 57.00 Old road, bears E. and W.  
 80.00 Set an iron post, 3 ft. long, 2 ins. dia., 20 ins. in the  
 ground to solid rock, in a mound of stone, for the cor.  
 of secs. 6 and 7 only, with brass cap mkd

T18N  
 R53E | R54E  
 S6  
 S7  
 1924

At base of post deposit a marked(x)stone, 1x3x4 ins.

Land, rolling mountainous. Soil, gravelly loam.

Timber, none. Undergrowth, sagebrush.

Fair grazing. General drainage, E.

North, on true W. bdy. of township

Asc. SW. slope 15 ft. to

2.50 Ridge (summit of range), bears W. and SE.

Desc. general NE. slope 150 ft. to

40.00 Set an iron post, 3 ft. long, 1 in. dia., 27 ins. in the  
 ground, for  $\frac{1}{4}$  sec. cor. of sec. 6 only, with brass cap  
 mkd

$\frac{1}{4}$   
 S6  
 1924

At base of post deposit a marked(x)stone, 2x2x2 ins.

45.00 Asc. SE. slope 30 ft. to

57.00 Desc. NE. slope 120 ft. to

70.60 Ravine, drains NE. Asc. along NE. slope 30 ft. to

76.22 Intersect N. bdy. of township, and

Set an iron post, 3 ft. long, 3 ins. dia., 20 ins. in the  
 ground to solid rock, in a mound of stone, for the cor.  
 of Ts. 18 and 19 N., Rs. 53 and 54 E., with brass cap  
 mkd

T19N  
 R53E | R54E  
 S36 | S31  
 S1 | S6  
 T18N  
 1924

At base of post deposit a marked(x)stone, 1x3x4 ins.

*and hole*